

MULTI LUBE ECO

DESCRIPTION

Multi Lube Eco is a readily biodegradable high-performance lubricant. It's a thin, transparent and highly penetrative multi-purpose, 5 in 1 product; Lubricant, Protector, Cleaner, Loosening & Moisture repellent.

NSF-registered as a lubricant with incidental food contact, in and around food processing areas (H1).

PROPERTIES

- High performance universal lubricant, providing precision lubrication
- Repels moisture, thus preventing loss of voltage and short circuits in electrical installations
- Due to its high penetrating power, it breaks through even the thickest layers of rust and dirt. Loosening rusted frozen joints even in difficult to reach places
- Provides protection by leaving a thin, invisible film that seals off the metal surfaces preventing oxidation
- Safe for use on most metal parts, paintwork, rubber, plastic and carbon. Always test on an inconspicuous area before use
- Free from PTFE (PFAS) and silicone
- Included in the Green Line premium product range
- High proportion bio-based ingredients
- High % of Readily Biodegradable content
- Bio-LPG - Certified bioLPG propellant with CO2 reduction up to 90%, naturally produced via organic waste

FIELD OF APPLICATION

- Universal lubricant for locks, hinges, slides, instruments, paper and printing machines, firearms, mechanical parts, etc.
- Prevents electrical surge loss in plug leads, distributors, alternators, regulators, starting motors, switches, lighting, etc.
- Prevents oxidation and corrosion of exposed contacts, cables, battery terminals, fuses, tools, etc.
- Removes tar and light dirt from machines and surfaces while protecting them
- Quickly loosens rusted joints and fasteners, exhaust pipes, etc.
- Safer choice where a release into the environment is possible

USER INSTRUCTIONS

Shake can before use. Apply on dry and clean surfaces.
Spray from a distance of 15-20 cm.



MULTI LUBE ECO - MUE - 138

Art.no. 20103, 20104 & 20107

Signature: JH

Date: 2025-10-24

This document is the property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company must point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.

MULTI LUBE ECO

TECHNICAL DETAILS

Packaging:	500 ml bluemint® tin can aerosol ¹ . Art.no. 20103 100 ml alu. can aerosol: Art.no. 20107 5L Eco Box. Art.no. 20104
Color:	Colorless
Odor:	Mild
Propellant:	Propane/Butane
Base Oil	Fatty acid esters
Additives:	No
PFAS:	No
Application & Surface temperature:	-10°C to +50°C
Temperature resist:	-20°C to +190°C
Density (20°C):	0,75 g/cm ³ , bulk 0,86 g/cm ³
VOC (directive 2010/75 EG):	24,5 % (183 g/l), bulk 0 % (0 g/l)
Shelf life (temp.+5°C to +25 °C):	36 months
Readily biodegradable content:	100 %
Accessories:	Air Mix Multi Lube Eco. Art.no 15215-19 Tap 5l/15l Eco Box: Art.no. 35204 Can fix. Art.no 35912
Miscellaneous:	In compliance with the legal regulations, please see current Material Safety Data Sheet. https://veidec.com/en/msds
User instructions:	Scan the QR-code for MSDS, video and other information.




VEIDEC FEATURES



GREEN LINE
Our premium product range with focus on the environment and health as well as quality



READILY BIODEGRADABLE
100% of the product is readily biodegradable



Bio-LPG
With lower carbon dioxide net emission (aerosol)



UP-AND-DOWN
The aerosol can be used upside down



Product must be shaken before use

CERTIFICATES/REGISTRATIONS



Registered at NSF, products meeting the criteria for use in or around food-processing areas: category H1
[VEIDEC NSF listing](#)



Registered at BASTA:
ALFA

¹ Canister in bluemint® recycled steel and with a certified production method, CO2 emissions are reduced by 64%, compared to conventional steel.

MULTI LUBE ECO - MUE - 138	Art.no. 20103, 20104 & 20107
Signature: JH	Date: 2025-10-24
This document is the property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company must point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.	